


KA SERIES

Sprayers with cross-axial blowers
24", 28", and 32" diameters.



KA24

Fiberglass tank capacity 1,000 l - 2,000 l
Air capacity 18./28,000 m³/h



Test number: G1366



KA28

Fiberglass tank capacity 1,000 l - 2,000 l
Air capacity 25./31,000 m³/h




Test number: G1652



KA32

Fiberglass tank capacity 1,000 l - 2,000 l
Air capacity 38./45,000 m³/h



Test number: G1518

Type	Output (m ³ /h)	Pump (l/bar)	Required power (KVT)	Nozzles Quantity	Length (mm)	Tank width (mm)	blower width (mm)	Height (mm)	Empty weight (kg)	Row spacing min. (m)	Row spacing max. (m)	Cultural processing height max. (m)
KA24/1000-140	18./28.000	140/50	9,1	12	3260	1180	900	1820	703	1.5	2.4	2.5
KA24/1500-140	18./28.000	140/50	9,1	12	3420	1230	900	1750	723	1.5	2.4	2.5
KA24/2000-140	18./28.000	140/50	9,1	12	3785	1310	900	1910	738	1.5	2.4	2.5
KA28/1000-140	25./31.000	140/50	6,5	14	3310	1180	1100	1850	651	1.7	3.5	3
KA28/1500-140	25./31.000	140/50	6,5	14	3480	1230	1100	1840	744	1.7	3.5	3
KA28/2000-140	25./31.000	140/50	6,5	14	3845	1310	1100	1970	774	1.7	3.5	3
KA32/1000-140	38./45.000	140/50	14	16	3430	1180	1200	2010	691	1.8	5	3.5
KA32/1500-140	38./45.000	140/50	14	16	3620	1230	1200	2130	757	1.8	5	3.5
KA32/2000-140	38./45.000	140/50	14	16	3935	1310	1200	2200	765	1.8	5	3.5