

K-SERIES

Sprayers with cross-axial blowers
32", 36" and 42" diameters.



K32GA



Fiberglass tank capacity 1,000 - 2,000 liters
Air capacity 38./45,000 m³/h



K36GA



Fiberglass tank with a capacity of 1,000 - 2,000 liters
Air capacity 45./60.000 m³/h



Test number: G1731, 36 inches



K42GA



Fiberglass tank volume 1.000 l - 2.000 l
Air capacity 80./105.000 m³/h

Type	Output (m ³ /h)	Pump - (l/bar)	Required power (KVT)	Nozzles Quantity	Length (mm)	Tank width (mm)	blower width (mm)	Height (mm)	Empty weight (kg)	Row spacing min. (m)	Row spacing max. (m)	Cultural processing height max. (m)
K32GA/1000-140	38./45.000	140/50	14	16		1180	1020			1.8	5	5
K32GA/1500-140	38./45.000	140/50	14	16		1230	1020			1.8	5	5
K32GA/2000-140	38./45.000	140/50	14	16		1310	1020			1.8	5	5
K36GA/1000-140	45./60.000	140/50	18,2	16	3550	1180	1150	2020	707	1.8	5	4.5
K36GA/1500-140	45./60.000	140/50	18,2	16	3750	1230	1150	2060	733	1.8	5	4.5
K36GA/2000-140	45./60.000	140/50	18,2	16	4050	1310	1150	2100	893	1.8	5	4.5
K42GA/1000-140	80./105.000	140/50	26,9	16		1180	1250	2130	725	1.8	7	6
K42GA/1500-140	80./105.000	140/50	26,9	16		1230	1250	2170	750	1.8	7	6
K42GA/2000-140	80./105.000	140/50	26,9	16	4140	1310	1250	2210	905	1.8	7	6